


NOTES:

- AIR SUPPLY SPECIFICATIONS:
- ISO 8573.1 CLASS 3.3.3 AIR SUPPLY OR BETTER RECOMMENDED
 - FOR MATRIX OR FLY HEIGHT/INPUT PRESSURE/VACUUM PRESSURE REQUIREMENTS, SEE NEW WAY LITERATURE

- MATERIAL SPECIFICATIONS:
- CONVEYOR BASE: ANODIZED ALUMINUM
 - CONVEYOR FACE: POROUS CARBON

PROPRIETARY ITEM:

THIS DRAWING CONTAINS INFORMATION PROPRIETARY TO NEW WAY MACHINE COMPONENTS, INC. ANY REPRODUCTION, DISCLOSURE, OR USE OF THIS DRAWING OR THE INFORMATION CONTAINED HEREIN IS EXPRESSLY PROHIBITED EXCEPT AS NEW WAY MAY OTHERWISE AGREE TO IN WRITING. ALL RIGHTS RESERVED BY NEW WAY MACHINE COMPONENTS, INC.

TOLERANCES UNLESS OTHERWISE SPECIFIED		TITLE: HIGH SPEED FLAT PANEL CONVEYOR		<div>NEWWAY[®]</div> <div>air bearings</div>		
ANGLES \pm 1/2° DECIMALS .xx \pm .010 DECIMALS .xxx \pm .005 FRACTIONS \pm 1/64		DRAWN: EJS	DATE: 5/10/2016			MATERIAL:
SURFACE ROUGHNESS 63  RMS MAX.		CHECKED:	DATE:	HEAT TREAT:	EWO. NO.	—
BREAK ALL SHARP EDGES .005-.020		SCALE: 1:3	SHT. 1 OF 1	FINISH: CONVEYOR BASE: BLUE ANODIZE_ MIL-A-8625 TYPE 2, CLASS 2	DWG. NO.	S22100H1000
		USED ON: —			REV.	-.03