



NOTES:

- AIR SUPPLY SPECIFICATIONS:
- ISO 8573.1 CLASS 3.3.3 AIR SUPPLY OR BETTER RECOMMENDED
 - FOR MATRIX OR FLY HEIGHT/INPUT PRESSURE/VACUUM PRESSURE REQUIREMENTS, SEE NEW WAY LITERATURE

- MATERIAL SPECIFICATIONS:
- CONVEYOR BASE: ANODIZED ALUMINUM
 - CONVEYOR FACE: POROUS CARBON

PROPRIETARY ITEM:

THIS DRAWING CONTAINS INFORMATION PROPRIETARY TO NEW WAY MACHINE COMPONENTS, INC. ANY REPRODUCTION, DISCLOSURE, OR USE OF THIS DRAWING OR THE INFORMATION CONTAINED HEREIN IS EXPRESSLY PROHIBITED EXCEPT AS NEW WAY MAY OTHERWISE AGREE TO IN WRITING. ALL RIGHTS RESERVED BY NEW WAY MACHINE COMPONENTS, INC.

TOLERANCES UNLESS OTHERWISE SPECIFIED			TITLE: HIGH SPEED FLAT PANEL CONVEYOR		NEWWAY[®] air bearings	
ANGLES \pm 1/2° DECIMALS .xx \pm .010 DECIMALS .xxx \pm .005 FRACTIONS \pm 1/64			DRAWN: EJS	DATE: 5/10/2016		
SURFACE ROUGHNESS 63 $\sqrt{\hspace{1.5cm}}$ RMS MAX. BREAK ALL SHARP EDGES			CHECKED:	DATE:	HEAT TREAT:	
.005-.020			SCALE: 1:3	SHT. 1 OF 1	FINISH: CONVEYOR BASE: BLUE ANODIZE_ MIL-A-8625 TYPE 2, CLASS 2	
			USED ON: -		DWG. NO. S22100H1250	REV. -.03