



NOTES:

AIR SUPPLY SPECIFICATIONS:

- ISO 8573.1 CLASS 3.3.3 AIR SUPPLY OR BETTER RECOMMENDED
- FOR MATRIX OR FLY HEIGHT/INPUT PRESSURE/VACUUM PRESSURE REQUIREMENTS, SEE NEW WAY PRODUCT LITERATURE

MATERIAL SPECIFICATIONS:

- CONVEYOR BASE: BLUE ANODIZED ALUMINUM
- CONVEYOR FACE: POROUS CARBON

PROPRIETARY ITEM:
THIS DRAWING CONTAINS INFORMATION PROPRIETARY TO NEW WAY MACHINE COMPONENTS, INC. ANY REPRODUCTION, DISCLOSURE, OR USE OF THIS DRAWING OR THE INFORMATION CONTAINED HEREIN IS EXPRESSLY PROHIBITED EXCEPT AS NEW WAY MAY OTHERWISE AGREE TO IN WRITING. ALL RIGHTS RESERVED BY NEW WAY MACHINE COMPONENTS, INC.

TOLERANCES UNLESS OTHERWISE SPECIFIED ANGLES: \sphericalangle 12° DECIMALS: XX .010 DECIMALS: XXX .005 FRACTIONS: 1/64 SURFACE ROUGHNESS: 63 RMS MAX. BREAK ALL SHARP EDGES .005-.020	TITLE: HIGH SPEED FLAT PANEL CONVEYOR		NEWWAY air bearings
	DATE: 06/14/05	MATERIAL: SEE NOTES	
	SCALE: 1:2	SHT: 1 OF 1	HEAT TREAT: SEE NOTES
	USED ON:	FINISH: SEE NOTES	EWO. NO. DWG. NO. S22100H750 REV. A